600 S. Brandywine Ave. Downingtown, PA 19335 Phone: 610.518.6601

Fax: 610.518.6602 CustomerService@atlantexmfg.com

PYROTEX SNAPRECLOSABLE SNAP FIRESLEEVE



- Self-extinguishing thick-walled insulating sleeve for excellent thermal protection
- Sheds molten metal splash and protects systems from direct flame impingement
- Lightweight and highly flexible composite protective sleeve- exceptional elasticity
- Will not melt, burn, or support combustion— does not emit toxic smoke
- Resistant to hydraulic fluids, fuels, lubricating oil, and water
- Extends service life of assemblies and provides personnel protection

Product Description

Pyrotex SNAP Firesleeve provides the time-tested value of standard, seamless Pyrotex SG Firesleeve in an easy-to-install sleeve solution which can be installed without the need to disconnect existing lines.

Pyrotex SNAP is fabricated from either Pyrotex Industrial Knit or Pyrotex Aerospace-grade Braid Firesleeve, expertly fabricated with a high-temperature snap closure system. Pyrotex SNAP keeps your processes running, and allows for increased uptime and productivity by eliminating the need to disconnect lines in order to resleeve. Bundle multiple lines together with Pyrotex SNAP to provide simultaneous protection with one sleeve and to route hoses, wires, and cables away from hazards.

PYROTEX SNAP PART NUMBERS			
NOMINAL ID		AEROSPACE-GRADE BRAID	
3/4"	19mm	PT12200-## SNAP	
1"	25mm	PT16200-## SNAP	
1-1/4"	32mm	PT20200-## SNAP	
1-1/2"	38mm	PT24200-## SNAP	
1-3/4"	44mm	PT28200-## SNAP	
2"	51mm	PT32200-## SNAP	
2-1/4"	57mm	PT36200-## SNAP	
2-1/2"	64mm	PT40200-## SNAP	
2-3/4"	70mm	PT44200-## SNAP	
3"	76mm	PT48200-## SNAP	
3-1/2"	89mm	PT56200-## SNAP	
4"	102mm	PT64200-## SNAP	

PYROTEX SNAP PART NUMBERS				
NOMINAL ID		INDUSTRIAL KNIT		
3/4"	19mm	PT12100-## SNAP		
1"	25mm	PT16100-## SNAP		
1-1/4"	32mm	PT20100-## SNAP		
1-1/2"	38mm	PT24100-## SNAP		
1-3/4"	44mm	PT28100-## SNAP		
2"	51mm	PT32100-## SNAP		
2-1/4"	57mm	PT36100-## SNAP		
2-1/2"	64mm	PT40100-## SNAP		
2-3/4"	70mm	PT44100-## SNAP		
3"	76mm	PT48100-## SNAP		
3-1/2"	89mm	PT56100-## SNAP		
4"	102mm	PT64100-## SNAP		
4"	102mm	PT64100-## SNAP		

WORKING TEMPERATURE

CONTINUOUS: 500°F / 260°C **SHORT TERM:** 2200°F / 1200°C

ADDED VALUE

- Simple, retrofit installation
- Atlantex's proven performance in an easy-to implement thermal solution
- Increase uptime & protect personnel

MATERIAL COMPOSITION

- Highly texturized E-Glass Fiber
- Braided or knitted insulating substrate
- High-temperature Silicone polymer
- SNAP closure

AVAILABILITY

- Pyrotex SNAP Braid is available in diameters from 3/4" (19mm) to 5" (127mm)
- Fabricate Pyrotex SG Blanket for sleeving larger than 5" (127mm)
- Available in standard RIO, other colors are available upon request

