



WORKING TEMPERATURE

CONTINUOUS: 320°F / 160°C

SHORT TERM: 570°F / 300°C

ADDED VALUE

- Excellent cut-through protection
- Highly durable protective sleeve
- Bundle multiple lines together
- Free of halogens & asbestos

MATERIAL COMPOSITION

- 3000 Denier Ballistic-grade Kevlar®
- Boldly colored Saturant
- Tightly braided construction
- Low weight & extremely high strength
- 100% genuine Kevlar® fibers

VERSATILE PROTECTION

- Ultimate cut-through protection
- Abrasion/Wear resistance
- Assemblies remain flexible
- Non-irritating fiber
- Natural color provides line visibility
- Great bundling solution
- Excellent thermal stability

APPLICATIONS

- Protection for hydraulic hoses, fuel lines, wires, cables, and many other systems
- Industrial, defense, automotive applications
- Extreme protection for critical components when failure is not an option

AVAILABILITY

- Available colors: Safety Orange, Black, Blue, Red, and Green
- Bulk lengths available for scrap reduction
- Customized sleeve solutions available



ISO 9001
2ML-SAI Global

KEVTEX C BRAIDED COLORED CUT-RESISTANT SLEEVE



- Kevlar® aramid sleeving braided by Atlantex to provide heavy duty protection for critical lines in harsh, hazardous environments
- KevTex C exhibits great thermal stability, and will not support combustion
- Kevlar® offers extremely high tensile strength, high modulus, and toughness proven in some of the most demanding applications
- Dense braided construction offers 100% system coverage while remaining flexible, expandable, and lightweight

Product Description

Atlantex's KevTex Kevlar® protective sleeving combines the time-tested physical strength of genuine Kevlar® fibers with our technical textile production expertise to create the ultimate in cut-resistant sleeving. Braided construction provides 100% system coverage and excellent flexibility. Manufactured with 100% genuine Kevlar® aramid fibers to ensure high performance in the most demanding applications.

Frequently used as a lightweight cut-through and wear-resistant sleeve over critical hoses, cables, and assemblies. KevTex C can also be used as an integral reinforcement layer for a wide range of products and industries.

Material Resistivity

- Cut-through resistance = Excellent
- Wear resistance = Excellent
- Dilute acid resistance = Very Good
- Dilute base resistance = Very Good
- Water resistance = Very Good
- Oil resistance = Very Good
- Fuel resistance = Very Good
- Solvent resistance = Very Good

*Avoid direct exposure to sunlight;
Sleeve will discolor in fluorescent light with no impact on performance*

KEVTEX C PART NUMBERS

SLEEVE ID		STANDARD LENGTHS	PART NO
1/4"	6 mm	100ft.	KS04200-##
1/2"	13 mm	100ft.	KS08200-##
3/4"	19 mm	100ft.	KS12200-##
1"	25 mm	100ft.	KS16200-##
1-1/4"	32 mm	100ft.	KS20200-##
1-1/2"	38 mm	100ft.	KS24200-##
1-3/4"	44 mm	100ft.	KS28200-##
2"	51 mm	100ft.	KS32200-##
2-1/2"	64 mm	100ft.	KS40200-##
3"	76 mm	100ft.	KS48200-##
4"	102 mm	100ft.	KS64200-##

ATLANTEX COLOR CODES (-##)

-15	Safety Orange	
-30	Black	
-60	Blue	
-70	"Fire Engine Red"	
-80	Green	